





MOTOR AND SHAFT PINIONS

JDN MONOCRANE Motor and Shaft Pinions are machine cut from K1045, providing both strength and durability with the option of flame hardening.

Alternative materials available upon request as well as special sizes.



SHAFT PINION



MOTOR PINION

PART No. DESIGNATION

P Pinion
2 Module
24 No of Teeth
20 Shaft Size
M or S Motor or Shaft

PART No	MODULE	No of TEETH	D	O	P	Q	R	S		U
P22420M	2	24	20	52	-	-	45	60	22.8	6
P22425M	2	24	25	52	-	-	45	60	28.3	8
P22425S	2	24	25	52	18	28	-	-	28.3	8
P31920M	3	19	20	63	-	-	45	60	22.8	6
P31925M	3	19	25	63	-	-	45	60	28.3	8
P31930M	3	19	30	63	-	-	45	60	33.3	8
P31930S	3	19	30	63	30	49	-	-	33.3	8
P31935M	3	19	35	63	-	-	45	60	39	10
P32420M	3	24	20	78	-	-	45	60	22.8	6
P32420S	3	24	20	78	30	49	-	-	23	6
P32425M	3	24	25	78	-	-	45	60	28.3	8
P32425S	3	24	25	78	30	49	-	-	29	8
P32430M	3	24	30	78	-	-	45	60	33.3	8
P32430S	3	24	30	78	30	49	-	-	33.3	8
P32435M	3	24	35	78	-	-	45	60	39	10
P32435S	3	24	35	78	30	49	-	-	39	10
P32440M	3	24	40	78	-	-	45	60	43.3	12
P32440S	3	24	40	78	30	49	-	-	44	12
P33020M	3	30	20	96	-	-	45	60	22.8	6
P33020S	3	30	20	96	30	49	-	-	23	6
P33025M	3	30	25	96	-	-	45	60	28.3	8
P33030M	3	30	30	96	-	-	45	60	33.3	8
P33030S	3	30	30	96	30	49	-	-	33.3	8
P33040M	3	30	40	96	-	-	45	60	43.3	12
P33040S	3	30	40	96	30	49	-	-	44	12
P41925M	4	19	25	84	-	-	55	75	28.3	8
P41930M	4	19	30	84	-	-	55	75	33.3	8
P41930S	4	19	30	84	55	70	-	-	33.3	8
P41935M	4	19	35	84	-	-	55	75	39	10
P41940M	4	19	40	84	-	-	65	85	43.3	12
P41940S	4	19	40	84	55	70	-	-	43.3	12
P42430M	4	24	30	104	-	-	55	75	33.3	8
P42435S	4	24	35	104	55	70	-	-	39	10
P42440M	4	24	40	104	-	-	65	85	43.3	12
P42440S	4	24	40	104	55	70	-	-	43.3	12
P42450M	4	24	50	104	-	-	65	85	54	14
P51925M	5	19	25	105	-	-	65	85	28.3	8
P51930M	5	19	30	105	-	-	65	85	33.3	8
P51935M	5	19	35	105	-	-	65	85	39	10
P51940M	5	19	40	105	-	-	65	85	43.3	12
P51950M	5	19	50	105	-	-	65	85	53.8	14
P51950S	5	19	50	105	60	80	-	-	53.8	14
P52430M	5	24	30	130	-	-	65	85	33.3	8
P52440M	5	24	40	130	-	-	65	85	43.3	12
P52440S	5	24	40	130	60	80	-	-	44	12
P52450S	5	24	50	130	60	80	-	-	53.8	14
P62450S	6	24	50	156	70	100	-	-	54	14
P62460M	6	24	60	156	-	-	85	115	65	18
P62470M	6	24	70	156	-	-	110	140	75	20

* All dimensions in mm and subject to change without notice.